


NOTES

1. AERIAL IS FSA NAIP 2006.
2. EDGE OF WATER AS DRAWN DIFFERS FROM AERIAL IMAGE DUE TO FIELD CONDITIONS OBSERVED IN 2007 AND OTHER FACTORS.
3. TOP OF WATER ELEVATION 973.05 AS OF JULY 12, 2007.
4. AREAS NUMBERED AND CONTAINED WITHIN YELLOW DASHES REFLECT POTENTIAL STAGING OF DREDGE QUANTITIES. ACTUAL DREDGE QUANTITIES AND LOCATIONS WILL BE DEPENDENT ON CONTRACTOR BIDS.
5. AREAS 1 THRU 4 EACH REFLECT A DREDGE RANGE OF ROUGHLY 125,000 TO 150,000 CUBIC YARDS. AREA 5 REFLECTS ROUGHLY 75,000 CUBIC YARDS.
6. EXISTING SCOUR HOLES (FIG. 9) IN SETBACK ZONE WILL NOT BE FILLED. PROPOSED CONTOURS WILL BE CONSTRUCTED TO MATCH EXISTING SCOUR DEPTHS OUTSIDE OF 25'-FOOT SETBACK.
7. DISTANCE OF SETBACK FROM EXISTING DAM FACE TO BE DETERMINED.

LEGEND

- LESS THAN 5'
- 5' TO 10'
- 10' TO 15'
- 15' TO 20'
- 25' SETBACK FROM SHORE
- PROPOSED BOTTOM ELEVATION 969

No.	Revision	Date	By



HE
Houston Engineering, Inc.
 6901 EAST FISH LAKE ROAD, SUITE 140 TEL: (763) 493-4522
 MAPLE GROVE, MINNESOTA 55369 FAX: (763) 493-5572

Drawn by	DJL	Date	08/03/07
Checked by	WSP	Scale	AS SHOWN

LAKE REDWOOD
 PROPOSED CONDITIONS
 REDWOOD FALLS, MINNESOTA